

SPECIFICATIONS - SPEED TRIPLE R

ENGINE AND TRANSMISSION		
Type	Liquid-cooled, 12 valve, DOHC, in-line 3-cylinder	
Capacity	1050cc	
Bore/Stroke	79 x 71.4mm	
Fuel System	Multipoint sequential electronic fuel injection with SAI	
Exhaust	Stainless steel 3 into 1 into 2, twin high level stainless steel silencers	
Final Drive	X ring chain	
Clutch	Wet, multi-plate	
Gearbox	6-speed	
Oil Capacity	3.8 litres (1.0 US gals)	
CHASSIS, RUNNING GEAR AND DISPLAYS		
Frame	Aluminum beam twin-spar	
Swingarm	Single-sided, aluminum alloy with eccentric chain adjuster	
Wheels	Front	Forged aluminum alloy 5 spoke 17 x 3.5in
	Rear	Forged aluminum alloy 5 spoke 17 x 6.0in
Tires	Front	120/70 ZR17
	Rear	190/55 ZR17
Suspension	Front	Öhlins 43mm NIX30 upside down forks with adjustable rebound and compression damping, 120mm travel
	Rear	Öhlins TTX3 twin tube Monoshock with rebound and compression damping, 130mm rear wheel travel
Brakes	Front	Twin 320mm floating discs, Brembo 4-piston Mobobloc radial calipers, switchable ABS
	Rear	Single 255mm disc, Nissin single 2-piston sliding caliper, switchable ABS
Front Brake Master Cylinder	Brembo radial master cylinder, 18mm diameter	
Instrument Display/Functions	LCD multi-functional instrument pack with digital speedometer, fuel gauge, trip computer, analogue tachometer, programmable gear change lights, lap timer, service interval announcement and TPMS ready, switchable ABS	
DIMENSIONS AND CAPACITIES		
Length	2100mm (82.1in)	
Width	795mm (31.3in)	
Height without mirrors	1110mm (43.7in)	
Seat Height	825mm (32.5in)	
Wheelbase	1435mm (56.5in)	
Rake/Trail	22.8°/90.9mm	
Fuel Tank Capacity	17.5 litres (4.6 US gals)	
Wet Weight (ready to ride)	212kg (466lbs)	
PERFORMANCE		
(Measured at crankshaft to 95/1/EC)		
Maximum Power	135PS / 133bhp / 99kW @ 9400rpm	
Maximum Torque	111Nm 82ft.lbs @ 7750rpm	
FUEL EFFICIENCY		
City	34 MPG	
Highway	50 MPG	