

SPECIFICATIONS - STREET TRIPLE

ENGINE AND TRANSMISSION		
Type	Liquid-cooled, 12 valve, DOHC, in-line 3-cylinder	
Capacity	675cc	
Bore/Stroke	74 x 52.3mm	
Fuel System	Multipoint sequential electronic fuel injection with SAI	
Exhaust	Stainless steel 3 into 1 into 2 exhaust system with twin high level polished stainless steel silencers	
Final Drive	O ring chain	
Clutch	Wet, multi-plate	
Gearbox	6-speed, close ratio	
Oil Capacity	3.5 litres (0.9 US gals)	
CHASSIS, RUNNING GEAR AND DISPLAYS		
Frame	Aluminum beam twin-spar	
Swingarm	Braced, twin-sided, cast aluminum alloy	
Wheels	Front	Cast aluminum alloy 5-spoke 17 x 3.5in
	Rear	Cast aluminum alloy 5-spoke 17 x 5.5in
Tires	Front	120/70 ZR17
	Rear	180/55 ZR17
Suspension	Front	Kayaba 41mm upside down forks, 120mm travel
	Rear	Kayaba monoshock 126mm rear wheel travel
Brakes	Front	Twin 308mm floating discs, Nissin 2-piston sliding caliper
	Rear	Single 220mm disc, Nissin single piston caliper
Front Brake Master Cylinder	Nissin integrated reservoir master cylinder 14mm diameter	
Instrument Display/Functions	LCD multi-functional instrument pack with digital speedometer, trip computer, analogue tachometer, lap timer, gear position indicator, programmable gear change lights and clock	
DIMENSIONS AND CAPACITIES		
Length	2000mm (78.7in)	
Width	735mm (28.9in)	
Height without mirrors	1060mm (41.7in)	
Seat Height	800mm (31.5in)	
Wheelbase	1410mm (55.5in)	
Rake/Trail	24.3°/95.3mm	
Fuel Tank Capacity	17.4 litres (4.6 US gals)	
Wet Weight (ready to ride)	189kg (416lbs)	
PERFORMANCE		
(Measured at crankshaft to 95/1/EC)		
Maximum Power	106PS / 105bhp / 78kW @ 11700rpm	
Maximum Torque	68Nm / 50ft.lbs @ 9200rpm	
FUEL EFFICIENCY		
City	33 MPG	
Highway	51 MPG	